REPORT DOCUMENTATION PAGE

Form Approved OMB NO. 0704-0188

Dublic Benesting burden for this collection of	information is estimated to average 1 hour per	response including the	time for reviewing instructions, searching existing data sources	
Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection				
of information, including suggestions for redu	cing this burden, to Washington Headquarters	Services, Directorate for	or information Operations and Reports, 1215 Jefferson Davis Highy	way,
Suite 1204, Arlington, VA 22202-4302, and to		work Reduction Project		\dashv
1. AGENCY USE ONLY (Leave Blank		-	3. REPORT TYPE AND DATES COVERED	
	20 Dec 00		FINAL 01 Aug 96 - 30 Apr 00	
			5. FUNDING NUMBERS	
4. TITLE AND SUBTITLE			5. FUNDING NUMBERS	
Visual Communications: The Next Generation - Compression, Access, and		DAAH04-96-1-0342		
Delivery of Visual Information			DAA1104-30-1-0342	
6. AUTHOR(S)			-	
Kannan Ramchandran				4.
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMING ORGANIZATION	
University of Illinois - Urbana @ Champaign			REPORT NUMBER	
Committee of the commit				
9. SPONSORING / MONITORING AC	GENCY NAME(S) AND ADDRESS(ES		10. SPONSORING / MONITORING	
			AGENCY REPORT NUMBER	
U. S. Army Research Office	ce		4 DO 05004 40 OLV//D	
P.O. Box 12211			ARO 35604.12-CI-YIP	
Research Triangle Park, NC 27709-2211				
Research Frangie Faik, I	27705 2211			
11. SUPPLEMENTARY NOTES				
	findings contained in this report	are those of the	author(s) and should not be construed as an off	icial
	n, policy or decision, unless so d			10141
Department of the Army position	ii, policy of decision, unless so d	esignated by our	er documentation.	
12 a. DISTRIBUTION / AVAILABILITY STATEMENT			12 b. DISTRIBUTION CODE	
12 d. DISTRIBUTION / AVAILABILETT STATEMENT			12 U. DISTRIBUTION CODE	
Approved for public release; distribution unlimited.				
Approved for public release,	distribution diffinited.		r	
13. ABSTRACT (Maximum 200 words)			
13. Abbilder (Maximum 200 World	,			
This ARO-YIP grant resulted in	the creation of novel paradigms	for the representa	tation, compression, and delivery over noisy	
channels and hetergeneous netv	orks of images and video. Sever	al publications re	esulted from this work and formed the core of tw	0
M.S. and one Ph.D. theses. The	projects included hybrid analog/o	ligital framework	for source-channel coding of images, region-ba	sed
video coding using mathematical	morphology, and multiresolution	al motion estimati	tion and video coding on wavelets.	
1		ויוכו	TO PTTAT THE POLICE	
DTIC QUALITY INCREGRED 4				
20010117 127				
		/ [UUTIITT <i>I TIT</i>	
		► \		
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			44 PRIOR CORP	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION	18. SECURITY CLASSIFICATION	10 SECUDITY	CLASSIFICATION 20. LIMITATION OF ABSTR	ACT
OR REPORT	ON THIS PAGE	OF ABSTRA		.101
UNCLASSIFIED	UNCLASSIFIED		ASSIFIED UL	

>PI:

>

> >

>

> >

> >

>

> >

>

>

>

> >

> >

>

>

>

>

>

>

>

> > >

> >

>

>

>

>

> >

>

>

>

>

> >

>

> >

>

in [1].

KANNAN RAMCHANDRAN

DANH04-96-1-0342

>AFFILIATION:

ECE DEPARTMENT, UC BERKELEY

>TITLE:

Visual Communications: The Next Generation - Compression,

Access, and Delivery of Visual Information

SUMMARY

>This ARO-YIP grant resulted in the creation of novel paradigms for the >representation, compression, and delivery over noisy channels and >heterogeneous networks of images and video. Several publications resulted >from this week, and this work formed the core of two M.S. and one Ph.D. >theses. A brief summary of the projects follows in the following >sections of this final report.

>1) Hybrid analog/digital framework for Source-Channel Coding of images


The aim of this project was to consider the problem of image transmission over wireless channels using joint source-channel coding. Inspired by both information-theoretic principles and realistic wavelet-based image models, we have advocated a novel practical wavelet-based framework for integrating analog and digital modes of communication for transmitting images over noisy, time-varying channels. Our goal was to maximize the end-to-end delivered image quality subject to constraints on power and bandwidth. We considered a hierarchy of increasingly more sophisticated statistical wavelet-based image models. Our proposed joint source-channel coding algorithm, founded on a hybrid analog-digital framework, is validated both theoretically by its attractive proximity to the information-theoretic bounds on the underlying statistical image model used, as well as empirically by its excellent performance on real natural images. Our results indicate possibly significant performance gains, of the order of 3 dB in PSNR, compared to conventional state-of-the-art "all digital" approaches to joint source-channel coding. Figure~\ref{system} gives a block diagram of

>2) Region-based video coding using mathematical morphology

the conventional and hybrid systems. Details can be found

The motivation in this project was to use ideas from mathematical morphology for region-based video coding. Motion estimation and compensation has always been a critical problem for video coding. Traditional video coders use block-based motion compensation, which is simple and regular but causes blocky artifacts. New generation video coding standards such as MPEG-4 calls for object-based approaches, which require understanding of the image semantics. In this project, we segmented the video frames into distinct regions, which intuitively correspond to moving physical objects. Then we estimated and coded the motion for each region. Regions could have arbitrary shape, and were found by "growing" from a "seed" using morphological operations.

A striking feature of this coder is that the segmentation is based on decoded information, therefore region shapes or contours do not need to be coded. Regions can be merged, pruned, propagated, and modified from frame to frame. The



```
coder performs among the best of current state-of-the-art
       region-based video coders, and outperforms MPEG-1 at around 1M bps
       (bits per second). Details of this work can be found in [2].
>3) Multiresolutional motion estimation and video coding based on wavelets
     Our objective in this project was to improve upon existing
     motion estimation schemes and tranform coding methods to come up
     with a video coder better than the state-of-the-art. We attempted
     to exploit the motion correspondences in a multiresolutional fashion.
     Specifically, we first code a coarse resolution version of the video
     frame, estimate a motion field from this coarse resolution, then
     apply it to predict the next finer resolution. Finally we coded the
     predicted difference of the finer resolution, then repeated the whole
     process for the next finer resolution, and so on. Wavelet transform
     provided the right tool for this framework, because of its inherent
     multiresolutional nature.
     In our work, it is found that motion relationship indeed bear
     considerable coherence across different resolution levels, but
     directly estimating them from wavelet coefficients is not feasible.
     A major problem is the aliasing noise resulted from downsampling
     operations in the transform. This problem is attacked by upsampling and
     filtering the coarser signals using a specially designed interpolation
     The coder can operate in two modes: A purely backward mode in which
     no motion information is coded. A backward/forward hybrid mode in
     which the encoder judiciously
     chooses to send motion information for certain areas or at certain
     resolutions for each frame, and the decisions are optimized using
     zerotree coding and dynamic programming. The
     complete coder is efficient, scalable, and robust over large range
     of bitrates. It is compared against MPEG-1, at high bitrates
>
     (0.5-1.5 Mb/s), and with H.263 at low bitrates
     (24-128 kb/s). It achieves typically a coding gain of 1 dB over
     both standards. See [3] for details.
>
>BIBLIOGRAPHY (JOURNAL PUBLICATIONS RESULTING FROM GRANT)
>[1] I. Kozintsev, K. Ramchandran, "Robust image transmission over
>energy-constrained time-varying channels using multiresolution joint
>source-channel coding", IEEE Transactions on Signal Processing, vol.46,
>(no.4), April 1998, pp.~1012-26.
>[2] X. Yang, K. Ramchandran, "A low-complexity region-based video coder
>using backward morphological motion field segmentation", IEEE
>Transactions on Image Processing}, vol.8, (no.3), March 1999, pp.~332-45.
>[3] X. Yang, K. Ramchandran, "Scalable wavelet video coding using
>aliasing-reduced hierarchical motion compensation," IEEE
>Transactions on Image Processing}, vol.9, (no.5), May 2000, pp.~778-91.
>
* Steven D. Williams......University of Illinois
```

^{*} Business Manager IICoordinated Science Lab.

^{*} Ph. (217) 333-6531......1308 W. Main St.